

Body Builder Varnish V4074 Material Safety Data Sheet

Date: 1-1-2012

	н	М	I	S	
Minimal Slight Moderate	Hazard 0 1 2	Ratings Serious Severe	3 4	Health Flammability Reactivity	1 1 0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR:Van Son Holland Ink Corporation of AmericaMANUFACTURER:888 Vets Hwy. Hauppauge, NY 11788Kustom BlendingEmergency Telephone:631-715-70007960 Kentucky IProduct Class:Printing ink additiveChemtrec 24 HourTrade Name:Body Builder VarnishManufacturer s Corporation

MANUFACTURER: Kustom Blending, Inc. 7960 Kentucky Drive, Florence KY 41042 Chemtrec 24 Hour Emergency No-800-424-9300 Manufacturer s Code ID: V4074

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNO.	W T %	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Propriet ary Mixture	NJTSRN-8000-1363	100	N/A	N/A	No
l					
New Jersey Trade Secret					
CAS/Registry Trade Secret Numbers					
provided on request by manufacturer					

3. HAZARDS IDENTIFICATION

OSHAHazard Communication 29 CFR 1910.1200Nore

4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE

Eye Contact Direct contact may cause irritation.

Skin Contact Prolonged contact or repeated exposure may cause irritation.

Inhalation Excess inhalation of mist or vapor may cause dizziness, nausea or irritation of nasal and respiratory passages. Ingestion May cause gastrointestinal irritation.

Medical Conditions aggravated by normal exposure Persons with dermatitis should avoid skin contat.

Target Organs Skin, eyes, lungs.

Primary Routes of entry Eyes, inhalation, dermal.

EMERGENCY FIRST AID PROCEDURES

Eye Contact Gently flush with large amounts of water until initation subsides. If initation persists, contact a physician. Skin Contact Remove contaminated clothing and wash thoroughly before reusing. Wash affected skin areas with soap and water. Seek medical attention if initation persists

Ingestion If swallowed, do not induce vomiting. Call a physician or poison control center. Inhalation Remove individual to fresh air.

5. FIRE FIGHTING MEASURES

æ

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released:W ipe up. Dispose of wipes in approved waste containers for flammable liquids. If petroleum hydrocarbon is used, provide sufficient vertilation. W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Avoid storage above 90 F. Keep containers closed when not in use. Other Precautions: None required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation Use sufficient ventilation. Protective Gloves Impermeable gloves recommended to prevent skin invitation and absorption. Respiratory Protection None required. Eye Protection Safety glasses recommended. Other Protection None recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 0 lbs./gallon Boiling Range °F:> N/A Vapor Density vs. Air: Heavier Density: 8.40 lbs./gallon ASTM D1475 Type of Odor: Resinous Appearance: Viscous Liquid Evaporation Rate vs. Butyl Acetate: Slower Percentage Volatile By Weight: 0-1% ASTM D2369 0 Grams/liter Method 24 Freezing Point °F: N/A Vapor Pressure: .N/A Specific Gravity: 1.02 Odor Threshold: High pH: N/A Coefficient of Water/oil Distribution: N/A

10. STABILITY AND REACTIVITY

Product Stability:StableConditions to Avoid:Strong oxidizing agents, acids and bases. Avoid storage above 90 F.
Keep containers closed when not in use.Hazardous DecompositionProducts: Carbon Monoxide, Carbon Dioxide and smoke.Hazardous Polymerization:W ill not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogen Contains no materials that are considered carcinogenic by National Toxicology Program (NIP), International Agency for Research on Cancer (IARC) or OSHA.

MutagenNo TeratogenNo Reproductive Toxicity No

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply.Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION DOT (HM 181) : Not required

Shipping Labels: None required

15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act)All ingredients listed in TSCA Inventory CERCLA Superfund 40CFR 117.302Contains no reportable materials					
SARA TileIII					
FDA					
approval for	direct or indirect contact with food.				
EINECS (European Economic Community) All ingredients listed.					
California Proposition 65None					
CONEG Legislation	Meets all current State and Heavy Metal limitations.				
Canadian WHMIS	Non-controlled product.				

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.