

Material Safety and Data Sheet prepared by Wim De Boer

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America 888 Vets Hwy. Hauppauge, NY 11788 Emergency Telephone: 631-715-7000 Product Class: Fan Apart Adhesive for NCR Paper Trade Name: Fan-A-Part Adhesive

Material Safety Data Sheet - Fan-A-Part Adhesive

Date: 1-1-2012

	н	Μ	I	S	
Minimal Slight Moderate	Hazard 0 1 2	Ratings Serious Severe	3 4	Health Flammability Reactivity	2 2 0

MANUFACTURER: Lanci Industries -HAR Adhesives Division 60 South Park, Bedford OH, 44146 Chemtrec 24 Hour Emergency No-800-424-9300 Manufacturer s Code ID: V2043

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNo.	₩Т%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Isopropyl Alcohol	67-63-0	7	400 ppm	400 ppm	No
Methyl Alcohol	67-56-1	7	200 ppm	200 ppm	No
			(skin)	(skin)	

3. HAZARDS IDENTIFICATION

OSHA Hazard Comunication 29 CFR 1910.1200 Isopropyl Alcohol, Methyl Alcohol

4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE
Eye ContactDirect contact may cause inritation.
Skin Contact Prolonged contact or repeated exposure may cause minor irritation.
Inhalation
of nasal and respiratory passages.
Ingestion
Medical Conditions aggravated by normal exposure: Eye, skin and respiratory disorders and nerve, liver and kidney
diseases.
Target Organs:Skin, eyes, lungs.
Primary Routes of entryEyes, inhalation, dermal.
EMERGENCY FIRST AID PROCEDURES
Eye Contact Flush with water at least 15 minutes. Get immediate medical attention.
Skin Contact:
thoroughly before reusing.
Ingestion
Inhalation
Get medical attention.

5. FIRE FIGHTING MEASURES

Flash Point	105 F (CC)
Explosion Limits	None
Extinguishing Media	W ater spray, dry chemical, carbon dioxide or foam.
Unusual Fire and Explosion Hazards	Combustible liquid.
Special Fire Fighting Procedures	W ear self-contained breathing apparatus. Water may be used to
	keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released:W ipe up. Dispose of wipes in approved waste containers. If petroleum hydrocarbon is used, provide sufficient ventilation.

W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Keep containers closed when not in use. Store in a cool, dry area. Use only in well ventilated area. Other Precautions: Avoid contact with sparks, flames and incompatible materials. Wear appropriate protective equipment.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Use sufficient ventilation. Protective Gloves: Neoprene gloves recommended. Respiratory Protection: NIOSH approved respirator Eye Protection: Chemical safety goggles recommended. Other Protection: Electrical equipment should be explosion proof.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 1.5 lbs./gallon Boiling Range °F:> N/A Vapor Density vs. Air: N/A Density: 8.2 lbs./gallon ASTMD1475 Type of Odor: Alcohol Appearance: White liquid Evaporation Rate vs. Butyl Acetate: Percentage Volatile By Weight: 15% ASTMD2369

150 Grams/liter Method 24 Freezing Point [°]F: N/A Vapor Pressure: N/A Specific Gravity: 0.99 Odor Threshold: N/A pH: N/A Coefficient of Water/oil Distribution: N/A

10. STABILITY AND REACTIVITY

 Product Stability:
 Stable

 Conditions to Avoid:
 Heat, sparks, open flames and other ignition sources. Avoid acids, oxidizing materials and alkalis.

 Hazardous Decomposition
 Products: CO, CO₂, and other toxic fumes.

 Hazardous Polymerization:
 W ill not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogen	Contains no materials that are considered carcinogenic by OSHA or the
5	National Toxicology Program (NIP), or the International Agency for Research on
	Cancer (IARC).
Mutagen	No
Teratogen	No
Reproductive Toxicity	No

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply.Ventilate spill area first. Remove any potential source of spark or flame. Contain spill, absorb on non-reactive material and placed in sealed containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION- DOT (HM 181) : Combustible liquid N.O.S. Shipping Labels: None

15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act)All CERCLA Superfund 40CFR 117.302Cor SARA TitleIIINo	ntains no reportable materials
FDA	This is not a food additive and would not have approval for
din	ect or indirect ant act with faal.
EINECS (European Economic Community) All	
California Proposition 65Non	
CONEG LegislationMee	ets all current State and Heavy Metal limitations.
Canadian WHMISCon	trolled product.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.