

	н	М	I	S	
Minimal Slight Moderate	Hazard 0 1 2	Ratings Serious Severe	3 4	Health Flammability Reactivity	1 0 0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America 888 Vets Hwy. Hauppauge, NY 11788 Emergency Telephone: 631-715-7000 Product Class: Printing Ink Additive Trade Name: Van Son Fountain Stimulator MANUFACTURER: Tower Products, Inc. 2703 Freemansburg Ave. Easton, PA 18045 Chemtree 24 Hour Emergency No-800-424-9

Chemtrec 24 Hour Emergency No-800-424-9300 Manufacturers Code ID: V2153

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNo.	W T %	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Cobalt Acetate Tetrahydrate	71-48-7	8-15	.05mg/M3	.05mg/M3	No

3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910.1200 Cobalt as dust or fume.

4. FIRST AID MEASURES

	EFFECTS OF OVEREXPOSURE			
Eye ContactDirect contact may cause irritation.				
Skin Contact Prolonged contact or repeated exposure may cause minor irritation.				
Inhalation	Excess inhalation of mist or vapor may cause dizziness, nausea or irritation			
	of nasal and respiratory passages.			
Ingestion				
Medical Conditions appravated by normal exposure: Persons with dermatitis should avoid skin contact.				
Target Organs:Skin, eyes, lurgs.				
Primary Routes of entry				
	EMERGENCY FIRST AID PROCEDURES			
Eye Contact	Flush with large amounts of water until inritation subsides.			
	Finitation persists, contact a physician.			
Skin Contact:	W ash with soap and water. Remove contaminated clothing and wash			
	thoroughly before reusing.			
	If swallowed, do not induce vomiting. Call a physician.			
Inhalation	Remove individual to fresh air.			

5. FIRE FIGHTING MEASURES

Flash Point	Above 250 F Method used: closed cup
Explosion Limits	
Extinguishing Media	Foam, carbon dioxide, dry chemical. Water spray may be
	applied to cool exposed closed containers.
Unusual Fire and Explosion Hazards	Dense smoke may be generated when burning. Carbon
	Monoxide and Carbon Dioxide generated as combustion products
Special Fire Fighting Procedures	Self-contained breathing apparatus recommended.

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released:W ipe up. Dispose of wipes in approved waste containers. If petroleum hydrocarbon is used, provide sufficient vertilation.

W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Other Precautions: Avoid storage above 90 F. Keep containers closed when not in use. None required.

pH: N/A

0 Grams/liter Method 24

Freezing Point °F: -10 F

Specific Gravity: 1.01 Odor Threshold: Low

Vapor Pressure: less than 0.04ps

Coefficient of Water/oil Distribution: N/A

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Protective Gloves: Respiratory Protection: Use sufficient vertilation. Gloves recommended. None required. Eye Protection: Other Protection: Goggles recommended. None required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 0 lbs./gallon Boiling Range °F:> 200 Vapor Density vs. Air: Heavier Density: 8.35 lbs./gallon ASTM D1475 Type of Odor: Acetic Appearance: Ruple liquid Evaporation Rate vs. Butyl Acetate: Slower Percentage Volatile By Weight: 90% ASTM D2369

10. STABILITY AND REACTIVITY

Product Stability: Stable Conditions to Avoid: Strong oxidizing agents Avoid storage above 90 F. Keep containers closed when not in use. Hazardous Decomposition Products: None.

Products: None. Will not cour.

11. TOXICOLOGICAL INFORMATION

Hazardous Polymerization:

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION- DOT (HM 181) : Not required Shipping Labels: None required

15. REGULATORY INFORMATION

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.