

Material Safety Data Sheet So

Sonadry Colors Date 11/30/2006

	н	М	I	S	
Minimal Slight Moderate	0	Ratings Serious Severe	3 4	Health Flammability Reactivity	1 1 0

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR:Van Son Holland Ink Corporation of America<br/>185 Oval Drive Islandia, NY 11749MANUFACTURER:<br/>Chemtrec 24 Hou<br/>Manufacturer s C<br/>Manufacturer s CProduct Class:Of fæt Ink, oxidizing<br/>Sonadry ColorsManufacturer s C<br/>Manufacturer s C

MANUFACTURER: Van Son Royal Dutch Ink Factories Hilversum, Holland Chemtrec 24 Hour Emergency No-800-424-9300 Manufacturers Code ID: VS8010, 8011, 8012 VS 8030 - 8032, VS80100 - 80109

# 2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNO.	W T %	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Organic Pigments	Various	15-30	3.5mg/M3	3.5mg/M3	No
Synthetic Resins	Various	30-50	N/A	N/A	No
Severe Solvent Refined					
and Acid Treated Middle Distillate	64742-13-8				
	64741-91-9	20-40	N/A	N/A	No
Odbalt Drier	61789-52-4	0-1	0.1mg/M3	N/A	IARC
Manganese Drier	61788-58-7	0-1	5mg/M3	N/A	No
Polymeric Wax Blend	N/A	2-4	N/A	N/A	No

# 3. HAZARDS IDENTIFICATION

# 4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE				
Eye Contact				
Skin Contact Prolonged contact or repeated exposure may cause minor irritation.				
Inhalation Excess inhalation of mist or vapor may cause dizziness, nausea or irritat	ian			
of nasal and respiratory passages.				
Ingestion				
Medical Conditions aggravated by normal exposure: Persons with dematitis should avoid skin contact.				
Target Organs:Skin, eyes, lungs.				
Primary Routes of entry Eyes, inhalation, dermal.				
EMERGENCY FIRST AID PROCEDURES				
Eye Contact Flush with large amounts of water until invitation subsides.				
If initation persists, contact a physician.				
Skin Contact:				
thoroughly before reusing.				
Ingestion				
Inhalation				

# 5. FIRE FIGHTING MEASURES

Flash Point	Above 250 F Method used: closed cup
Explosion Limits	LEL: N/A UEL: N/A
Extinguishing Media	Foam, carbon dioxide, dry chemical. Water spray may be
	applied to cool exposed closed containers.
Unusual Fire and Explosion Hazards	Dense smoke may be generated when burning. Carbon
	Monoxide and Carbon Dioxide generated as combustion products
Special Fire Fighting Procedures	Self-contained breathing apparatus recommended.
6 ACCIDENTAL DELEACE MEACH	DEC

# 6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released:W ipe up. Dispose of wipes in approved waste containers. If petroleum hydrocarbon is used, provide sufficient ventilation.

W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

### 7. HANDLING AND STORAGE

Handling: Avoid storage above 90 F. Keep containers closed when not in use. Other Precautions: None required.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation:	Use sufficient ventilation.	Eye Protection:	Goggles recommended.
Protective Gloves:	Gloves recommended.	Other Protection:	None required.
Respiratory Protection:	None required.		

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 1.60-1.90 lbs./gallon	190-220 Grams/liter Method 24
Boiling Range °F:> 500-590	Freezing Point °F: N/A
Vapor Density vs. Air: Heavier	Vapor Pressure: less than 0.04psi
Density: 8.7-9.5 lbs./gallon ASTMD1475	Specific Gravity: 1.05-1.12
Type of Odor: Oily	Odor Threshold: High
Appearance: Colored viscous paste.	pH: N/A
Evaporation Rate vs. Butyl Acetate: Slower	Coefficient of Water/oil Distribution: N/A
Percentage Volatile By Weight: 20-25% ASTM D2369	

#### 10. STABILITY AND REACTIVITY

Stable
Strong oxidizing agents Avoid storage above 90 F.
Keep containers closed when not in use.
roducts: None.
Will not occur.

# 11. TOXICOLOGICAL INFORMATION

Carcinogen	Contains no materials that are considered carcinogenic by OSHA or the NIP.		
	International Agency for Research on Cancer (IARC)		
	classifies cobalt compounds as 2B carcinogens (possibly carcinogenic to humans)		
Mutagen	No		
Teratogen	No		
Reproductive Toxicity	No		

### 12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

#### 13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

# 14. TRANSPORT INFORMATION DOT (HM 181) : Not required Shipping Labels: None required

# 15. REGULATO RY INFORMATION

TSCA (Toxic Substance Control Act)All CERCLA Superfund 40CFR 117.302Com	
SARATileIII18	cobalt compound and 1% manganese compound
FDA	This printing ink is not a food additive and would not have
approval for	direct or indirect contact with food.
EINECS (European Economic Community) All	. ingredient s listed.
California Proposition 65No	ne
CONEG LegislationMee	ets all current State and Heavy Metal limitations.
Canadian WHMISCor	ntrolled product

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowl edge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designat ed herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.