



Material Safety Data Sheet - Van Son Blanket Fix

Date: 1-1-2012

		H	M	I	S
Hazard Ratings					
Minimal	0	Serious	3	Health	2
Slight	1	Severe	4	Flammability	1
Moderate	2			Reactivity	0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America
 888 Vets Hwy. Hauppauge, NY 11788
 Emergency Telephone: 631-715-7000
 Product Class: Blanket Repair Material
 Trade Name: Van Son Blanket Fix

MANUFACTURER: Tower Products, Inc.
 2703 Freemansburg Ave.
 Easton, PA 18045
 Chemtrec 24 Hour Emergency No-800-424-9300
 Manufacturer s Code ID: V2004

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CAS No.	W T %	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Cyclic Amine	872-50-4	95	N/A	N/A	No
Hydroxy Propyl Cellulose	9004-64-2	2-5	N/A	N/A	No

3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910.1200 None

4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE

Eye Contact Direct contact may cause severe irritation.
 Skin Contact Prolonged contact or repeated exposure may cause blistering.
 Inhalation Excess inhalation of mist or vapor may cause dizziness, nausea or irritation of nasal and respiratory passages.
 Ingestion May cause gastrointestinal irritation.
 Medical Conditions aggravated by normal exposure: Persons with dermatitis should avoid skin contact.
 Target Organs: Skin, eyes, lungs.
 Primary Routes of entry Eyes, inhalation, dermal.

EMERGENCY FIRST AID PROCEDURES

Eye Contact Gently flush with large amounts of water until irritation subsides. If irritation persists, contact a physician.
 Skin Contact : Wash with soap and water. Remove contaminated clothing and wash thoroughly before reusing. Seek medical attention if irritation persists
 Ingestion If swallowed, do not induce vomiting. Call a physician.
 Inhalation Remove individual to fresh air.

5. FIRE FIGHTING MEASURES

Flash Point Above 195 F Method used: closed cup
 Explosion Limits LEL: 1.3 / UEL: 9.5
 Extinguishing Media Foam, carbon dioxide, dry chemical. Water spray may be applied to cool exposed closed containers.
 Unusual Fire and Explosion Hazards Dense smoke may be generated when burning. Thermal decomposition causes toxic fumes.
 Special Fire Fighting Procedures Self-contained breathing apparatus recommended.

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: Wipe up. Dispose of wipes in approved waste containers.
 Vapors may ignite. Material partly water soluble. May float and spread.
 Waste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Avoid storage above 90 F. Keep containers closed when not in use to prevent degradation by moisture.
 Other Precautions: Do not breathe vapors. Do not get in eyes.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Use sufficient ventilation.

Protective Gloves: Impermeable gloves recommended.

Respiratory Protection: NIOSH Respirator during prolonged use.

Eye Protection: Safety glasses are recommended.

Other Protection: Apron, if splashing is possible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 1.68 lbs./gallon

Boiling Range °F: > 396

Vapor Density vs. Air: Heavier

Density: 8.60 lbs./gallon ASTM D1475

Type of Odor: Amine like

Appearance: Gel

Evaporation Rate vs. Butyl Acetate: Slower

Percentage Volatile By Weight: 95% ASTM D2369

200 Grams/liter Method 24

Freezing Point °F: N/A

Vapor Pressure: 0.29mm Hg

Specific Gravity: 1.03

Odor Threshold: High

pH: 10-11

Coefficient of Water/oil Distribution: N/A

10. STABILITY AND REACTIVITY

Product Stability: Stable

Conditions to Avoid: Strong oxidizing agents, acids and bases. Avoid storage above 90 F.
 Keep containers closed when not in use.

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide and smoke.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogen Contains no materials that are considered carcinogenic by OSHA or the National Toxicology Program (NTP), or the International Agency for Research on Cancer (IARC).

Mutagen No

Teratogen No

Reproductive Toxicity Yes

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION- DOT (HM 181) : Combustible Liquid N.O.S. NA1993 (NMP) Packaging Group III
 Shipping Labels: Combustible Liquid N.O.S.

15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act) All ingredients listed in TSCA Inventory

CERCLA Superfund 40CFR 117.302 Contains no reportable materials

SARA Title III None

FDA This product is not a food additive and would not have approval for direct or indirect contact with food.

EINECS (European Economic Community) All ingredients listed.

California Proposition 65 None

CONEG Legislation Meets all current State and Heavy Metal limitations.

Canadian WHMIS Non-controlled product

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.